

Yes to security. But without attracting attention. It is possible.
Mini-Dome - G-Cam/EFD-3266

Preliminary



GEUTEBRUCK's compact cameras perform at the accustomed high level. What's new: They operate discreetly. Who wants to be watched?

Product information

Thanks to switching between day/night and integrated invisible wide-range IR lighting, the camera offers an enormous energy-saving potential. The varifocal lens provides a clear view even for larger areas up to 25 meters without additional lighting.

Thanks to the Wide Dynamic Range function, it can clearly display objects in very dark and very light areas of the image. Important areas of the image can even be displayed more clearly in strong, glaring light.

The four configurable streams of the GEUTEBRUCK G-Scope make possible independent resolutions for live and recording as well as customized formats for the matrix display on the monitor. This relieves the load on your network and makes it possible to display numerous images with smooth playback.

The highlights

- Ideal for use in garages, freight forwarders or production halls.
- Cost-saving installation thanks to PoE
- Alternative power supply via 12VDC input available
- IP66 protection against environmental influences makes installation possible even in dusty or wet environments.
- Encrypted connection to the recorder secures your network against attacks, espionage or manipulated images.

GEUTEBRÜCK
Excellence in Video Security

Technical data

| | |
|---|---|
| Image sensor (Chip) | 1/2,8" Sony Progressive CMOS |
| Picture format | 16:9 |
| Video output (stream dependent) | Composite video: 1 Vpp, 75 Ohm (BNC) |
| Scanning system | Progressive scan |
| Mega pixel | 2 MP (Full HD) |
| Minimum sensitivity | 0.01 Lux (color), 0.001 Lux (B/W) |
| Day/Night function | Auto / on / off / smart |
| Wide Dynamic Range | Shutter WDR < 120 dB |
| White balance | Automatic / Manual / One Push ATW / Indoor / Outdoor |
| Exposure | Automatic / Manual |
| Shutter | 1/1.5 - 1/425 s |
| Digitale Noise Reduction | 2D/3D (low/middle/high/off) |
| Text overlay | Yes |
| Interface | Browser interface |
| B/W mode | Yes |
| OSD-Menu | English/German/French/Italian/Korean/Simplified Chinese/Traditional Chinese/Russian/Spanish/Japanese/Portuguese |
| Mirror-Function | Normal/Flip/Mirror H/180° Rotation |
| Portrait/Corridor View | Yes (stream dependent) |
| Compression | H.264, MJPEG |
| Picture rate (full resolution, dual stream) | PAL: H.264/50fps + H.264 or MJPEG:D1/50 fps |
| Resolutions | QCIF up to Full HD |
| Video Streaming | Quad Stream, configurable |
| Audio | 1x In, 1x Out/G.711, G.726 |
| Protocols | HTTP, HTTPS, TCP, FTP, RTSP, RTP, UDP, SMTP, SNMP, ICMP, IGMP, DHCP, UPnP, PPPoE, UPnP, QoS, ONVIF, IPv4/v6, IEEE802.1X |
| ONVIF compatible | Yes |
| Motion detection | Yes |
| Browser | Internet Explorer 6.0 and higher, Chrome, Firefox, Safari |
| Privacy masking | 5 adjustable masking zones (8 colors) |
| Picture Memory | µSD slot 32 GB max. |
| Lens | f = 2.8 mm |
| F-Stop | F2.0 |
| Camera angle adjustment range | Horizontal: +- 170°, Vertical: 20° ~ 90°, Turn: - |
| Operating temperature | - 10 °C to + 50 °C |
| Humidity in operation | 10 - 90 % rel. humidity (non condensing) |
| Voltage supply | 12 VDC or PoE (IEEE 802.3af) |
| Power consumption system | PoE: 6,24 W; 12 VDC: 5,24 W; IR + 0,36 W |
| IP class | IP 66 |
| Connectors | RJ-45 for 10/100 BASE-T Ethernet; Audio In/Out (2x 3.5 mm, Line in/out); DC power jack for external power supply; BNC female for analogue video output |
| Dimensions in mm (diameter x height) | 117 x 73 |
| Weight | Approx. 315 g |
| Certifications | FCC, CE, RoHS |
| Licensing | unit dependent (Gsc or G-Core) |
| Optional accessories | G-Cam/EBWM-007 (5.04742) Plastic wall mount G-Cam/EBDA-002 (5.04741) Mounting adapter G-Cam/EBWM-003 (5.04732) Metal wall mount G-Cam/EBTA-001 (5.04734) Bayonet to Thread adapter G-Cam/BPE-001 (5.04862) Pendant mount bracket G-Cam/EPMA-003 (5.04735) Pole mount adapter |
| Brand | GEUTEBRUCK |
| Order No. | 5.04715 |

Technical alterations reserved

GEUTEBRÜCK GmbH

Im Nassen 7-9 | D-53578 Windhagen | Tel. +49 (0)2645 137-0 | Fax-999 | E-mail: info@geutebrueck.com | Web: www.geutebrueck.com